


AD DRAFTING BY: M. BARAN	INITIALS	_ DATE: 10/19/11	1 ****** ANTERICANI Chicago: 105 W. Ma	adison St. Suite 170 cago, IL 60602
ALCULATIONS BY: NA				00 / Fax 312-277-20 I. Galena Avenue
HECKED BY: J. DYBAS			J BOIL BILLON TO C.	xon, IL 61021 31 / Fax 815-288-62
PPROVED BY: C. FIDIS			**************************************	ONAL DESIGN FIRI

<u>PEUPLES </u>	GAS	L I GH I	AND	CUKE	CUMPANY
	Н	/DROGRAPI	HIC SUR	RVEY	
NO	RTH BR	ANCH OF T	HE CHIC	CAGO RIV	'ER
FO	R NATU	RAL RESOL	JRCE TE	CHNOLO	GY

	REVISIONS	NORTH BRANCH CHICAGO RIVER	DRAWING NO.
DATE	DESCRIPTION	SEDIMENT INVESTIGATION	3 OF 6
		DATHYMETDIC MAD	DRAWING NAME
		BATHYMETRIC MAP	1 _ 3
		ASE PROJECT NO. 211090	A - J

NORTH BRANCH OF CHICAGO RIVER AT DIVISION ST. BRIDGE BATHYMETRIC MAP







CAD DRAFTING BY: M. BARAN	INITIALS DATE: 10/19/11	*****
CALCULATIONS BY: NA		*
CHECKED BY: J. DYBAS		
APPROVED BY: C. FIDIS		*****


*******	AMERICAN	Chicago:	105 W. Madison St. Suite 1700 Chicago, IL 60602 312-277-2000 / Fax 312-277-200 841 N. Galena Avenue
*****	SURVEYING & ENGINEERING, P.C. SURVEYORS • ENGINEERS SEODESISTS • MAPPING SCIENTISTS	ILLINOIS	Dixon, IL 61021 815-288-6231 / Fax 815-288-627 PROFESSIONAL DESIGN FIRM 003192

PEUPLES GAS LIGHT AND CUKE CUMPANY
HYDROGRAPHIC SURVEY
NORTH BRANCH OF THE CHICAGO RIVER
FOR NATURAL RESOURCE TECHNOLOGY

	REVISIONS	NORTH BRANCH CHICAGO RIVER	DRAWING NO.
DATE	DESCRIPTION	SEDIMENT INVESTIGATION	2 OF 6
			DRAWING NAME
		BATHYMETRIC MAP	Δ-2
		ASE PROJECT NO. 211090	A - 2









PROJECT REPORT ASE PROJECT #213002

DATE: MARCH 4, 2013

SUBMITTED BY

American Surveying & Engineering, P.C. 105 W. Madison St., Suite 1700

Chicago, IL 60602

T: 312-277-2000

F: 312-277-2002

www.americansurvey

Survey Report-

American Surveying & Engineering was contracted to provide bathymetric data detailing the existing conditions of the that part of the Chicago River lying on the North-Easterly side of Goose Island, from the North face of the Division Street Bridge South-Easterly along the river approximately 1800'.

Hydrographic Survey work on the Chicago River was performed using ASE's Survey Vessel the Abraham Lincoln, a 22' custom aluminum boat built by Scully's Boats. The survey was performed on January 30th, 2013 and utilized a Reson Seabat 7125 High Resolution Multi-beam Echosounder (MBE) and Edgetech's 4125 Side Scan Sonar (SSS) system. The Seabat 7125 is a single and/or dual frequency (200/400 kHz for a range of 500m/200m respectively) multi-beam echosounder system. The Edgetech 4125 Side Scan Sonar system utilizes 400 kHz/900 kHz simultaneous dual frequency full spectrum CHIRP technology and is equipped with on-board sensors which detect roll, pitch, heading and depth. It has a maximum range of 150 meters at 400 kHz and 75 meters at 900 kHz. Both the MBE and SSS sensors were mounted to a fixed side mount which is referenced to the center of gravity of the vessel and the water surface. Because site conditions were not optimal for using RTK GPS for data collection (specifically for MBE and SSS work), positions were provided using Differential GPS. Differential GPS utilizes dual mounted Trimble SPS852 receivers and an internal gyro which detects roll, pitch, and heading. River bottom elevations were determined depth measurements from the surface. This method of data collection works well in areas with bridges or other overhead obstructions which impair GPS signals. RTK GPS and differential leveling were used to establish and verify existing and new control points and benchmarks. Recovery forms were completed for two new site benchmarks on this project.

Survey lines were run along the river and spaced approximately eight feet apart for both MBE and SSS collection. This allowed for full coverage of the river bottom and provided significant overlapping areas. The areas of overlapping data were later compared against each other during post processing as an additional vertical check on the data collected. Comparison of overlapping data was used instead of a bar check due to the inability to maintain real-time GPS initialization.

For QA/QC purposes "pole check" shots were taken on the river bed using a Trimble R8 GPS receiver mounted on an extended rod using correction data provided by the Trimble VRSNow network. The rod was lowered from the front of the boat until resistance was met. Between check shots, when removing the rod from the river, it was noticed that the bottom consisted of a soft silt material. Though care was taken to set the bottom of the rod at the exact river bottom, it was observed that that the rod had sunk into the layer of soft silt as much as 1.5 feet. This was based on the amount of visible silt on the bottom of the rod in-between shots. This was then confirmed during post processing when the check shots were compared to the dtm produced from the MBE work. The resulting differences ranged between 0.116' and 1.204' vertically (check shots were lower in elevation than the dtm) which are in line with what field crews were

seeing in the field. Shots were also taken on the top of water throughout the project limits and found the average elevation of the river during the work to be at 575.79'.

Control Recovery Forms-

USACE Survey Marker Archi	<u>ve & Retrieval Tool Datash</u>	eet Type: New
Designation: BM/HS-AME-203-CHI		A PART OF THE PROPERTY OF THE
Project: 213002 NRT CHICAGO RIVER	A MILLION	The state of the s
Stamping: BM/HS-AME-203-CHI CDO 1985	THE REAL PROPERTY.	
PID NGS: NA COE:	The state of the s	
State: Illinois		1
County: COOK	DISK	
District: Chicago		JOY NEW YER W
Nearest Town: CHICAGO	The second of	
USGS Quad: LOOP		THE REAL PROPERTY.
T.R.S.: T39N R14E S4		A Dream
Nearest Hwy/Mi: I-90/I-94, 1.1 MILE	Machine Machine	
Date Recovered: 01/30/2013	- Horizontal -	- Vertical -
By: AMERICAN SURVEYING & ENGINEER !	Datum: NAD83 (2011)	Datum: NAVD88 ()
Condition/Stability: Good B	Lat: 41°54'01.3531" N	Elevation Ht: 586.867
Setting/Monument Type: BRASS DISK	Lon: -087°38'46.1393" W	Ellip Ht:
Owner: ACOE	Local Accuracy: 2-cm	Local Accuracy: 2-cm
GPS Suitable: Yes No	NSRS Accuracy: 2-cm	NSRS Accuracy: 2-cm
Obstructions: N E S W	Survey/Computation Method: RTK	Survey/Computation Method: Geodetic Levels
Magnetic: Yes No	Date Observed: 01/30/2013	Date Observed: 01/30/2013 Geoid09
Access:	Tidal/Hyduaylia	Gage Relationships -
	Owner: Gage ID: -El	evation Datum - Epoch:
2.7		
GOOSE ISLAND. FROM THE INTERSECTION OF W LEFT AT N KINGSBURY STREET. HEAD SOUTH W	EST THROUGH THE APARTMENT COMPLEX .E. OF THE NORTHERLY INTERSECTION OF T	H-WEST ALONG W HOBBIE ST AND TURN TO A CONCRETE WALK RUNNING ALONG THE CONCRETE WALK AND A WOODEN FENCE
Zone 1: IL EAST Northing 1: 1907036.12	JSFT Easting 1: 11713Z6.80USFT Conv	ergence 1: CSF 1:
Zone 2: Northing 2: [JSFT Easting 2: USFT Conv.	ergence 2: CSF 2:
- Horizon/Setup View -		- Close-Up View-
		GNEGO OGLICAN OGLICAN OGLICAN OGLICAN OGRIC
Required Fields In Red	ZOROBEZ ZOROBE	System Fields in Green

Submit System P

ds in Green
U-SMART ver 5.0
23 AUG 2012

	ontinued:							
e, using the old mples for horizon	der defined ac	curacy of t	the points,		ting that	into a va	Propagated	ers.
mples for horizon econd-order, cla ith average lengue econd-order, cla er square-root o	ntal and vert ass II horizon th line of 12 ass II levelin of the distance	curacy of t ical survey tal survey ,000 feet: g survey (t e in kilome	ys are: (that is to that is to eters) with	co say, 1:20, 1/20,000 = 0. say, 8 milling an average	,000) .600 feet	into a va	lue in mete	ers.
mples for horizone cond-order, classith average lengue cond-order, classic square-root cark spacing of 1.008 x SQRT [1.6]	ontal and vert ass II horizon th line of 12 ass II leveline of the distance mile (that i	curacy of the curacy of the curacy of the curvey (000 feet: grant survey (the in kilomes to say, 1 rs	ys are: (that is to 12,000 x 1 that is to eters) with	co say, 1:20, 1/20,000 = 0. say, 8 milling an average ters):	,000) .600 feet imeters bench	into a va	Propagated Error1 Error2 P.Error	ers.
apples for horizon apples for horizon accorder, classical apples for horizon accorder, classical apples for square-root on ark spacing of 1 008 x SQRT [1.6] fork accuracy for the NAD 8 original NAD 83 and 1.0 meters. Accuracy Refer to the control of the contro	ontal and vert ass II horizon th line of 12 ass II leveline of the distance mile (that in is) = 0.01 meter or horizontal of 3 coordinates (1986), then second, if the tence Network	curacy of to ical survey tal survey ,000 feet: g survey (te in kilomes to say, 1 rs geodetic co are consist the networe NAD 83 co (HARN) adjutett val	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	co say, 1:20, 1/20,000 = 0. say, 8 milling an average ters): ats can be estate originally has been deferred are the resulten the networker determined.	,000) .600 feet imeters bench stimated . NAD 83 .etermined .etermined .etermined .etermined .etermined	in two way adjustment to seldom statewide acy has be	Propagated Error1 Error2 P.Error s. , for example or regional en determination of the second of	ole,
aples for horizonaples for horizonaples for horizonaples for horizonaples for horizonaples for horizonaples for square-root of ark spacing of 1008 x SQRT [1.6] Fork accuracy for st, if the NAD 8 original NAD 83 and 1.0 meters. The Accuracy Reference for horizonaples for horiz	ontal and vert ass II horizon th line of 12 ass II leveline of the distance mile (that in is) = 0.01 meter or horizontal of 3 coordinates (1986), then second, if the tence Network	curacy of to ical survey tal survey ,000 feet: g survey (te in kilomes to say, 1 rs geodetic co are consist the networe NAD 83 co (HARN) adjutett val	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	co say, 1:20, 1/20,000 = 0. say, 8 milling an average ters): ats can be estate originally has been deferred are the resulten the networker determined.	one of a course of in place	in two way adjustment to seldom statewide acy has be	Propagated Error1 Error2 P.Error s. , for example or regional en determination of the second of	ole,
apples for horizon apples for horizon accond-order, classical accuracy for square-root of ark spacing of 1.008 x SQRT [1.60 order accuracy for the NAD 80 original NAD 80 orig	ontal and vert ass II horizon th line of 12 ass II leveline of the distance mile (that in is) = 0.01 meter or horizontal of 3 coordinates (1986), then Second, if the rence Network of if dataset,	curacy of to ical survey tal survey ,000 feet: g survey (te in kilomes to say, 1 rs geodetic co are consist the networe NAD 83 co (HARN) adjutett val	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	and convert co say, 1:20, 1/20,000 = 0. say, 8 milling an average cers): ats can be est the original y has been defented are the result enter the netwo enter determinated and the determi	,000) .600 feet imeters bench stimated . NAD 83 etermined . NAD 83 etermined . It of a . ork accurate and for no	in two way adjustment to seldom statewide acy has be etwork acc	Propagated Error1 Error2 P.Error s. , for example or regional en determination of the second of	ole,
aples for horizon cond-order, classical Accuracy:	ontal and vert ass II horizon th line of 12 ass II leveline of the distance mile (that in is) = 0.01 meter or horizontal of 3 coordinates (1986), then Second, if the rence Network of if dataset,	curacy of to ical survey tal survey ,000 feet: g survey (te in kilomes to say, 1 rs geodetic co are consist the networe NAD 83 co (HARN) adjutett val	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	and convert co say, 1:20, 1/20,000 = 0. say, 8 milling an average cers): ats can be est the original thas been deferming are the result cen determing could be used	,000) .600 feet imeters bench stimated . NAD 83 etermined . NAD 83 etermined . It of a . ork accurate and for no	in two way adjustment to seldom statewide acy has be etwork acc	Propagated Error1 Error2 P.Error s. or regional en determination determination determination determination desired as general value.	ole, ned to che area
aples for horizon cond-order, classical Accuracy:	ontal and vert ass II horizon ith line of 12 ass II leveline of the distance mile (that i. b) = 0.01 meter or horizontal coordinates (1986), then Second, if the sence Network coll meter. If diffic dataset, at Spacing (ft)	curacy of the control	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	and convert co say, 1:20, 1/20,000 = 0. say, 8 milling an average cers): ats can be est the original thas been deferming are the result cen determing could be used	one Distance	in two way adjustment to seldom statewide acy has be etwork acc e of these	Propagated Error1 Error2 P.Error s. for example or regional en determination determination determination determination desired as general value.	ole, led to che area
aples for horizon aples for horizon accond-order, classical accorder, classical accorder, classical accorder, classical accorder, classical accorder, classical accorder, classical accorder acc	portal and vert ass II horizon ith line of 12 ass II leveline of the distance in mile (that i i) = 0.01 meter is (1986), then second, if the second, if the second if the	curacy of to ical survey tal survey, 000 feet: g survey (te in kilomes to say, 1 rs geodetic control are consistent to the network the network then those feet	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	and convert co say, 1:20, 1/20,000 = 0. say, 8 milling an average cers): ats can be est the original thas been deferming are the result een determing could be used Average Line	one Distance	in two way adjustment to seldom statewide acy has be etwork acc e of these (ft) mete	Propagated Error1 Error2 P.Error s. for example or regional en determination determination determination general values for the gene	ole, ned to che area
aples for horizone acond-order, class the average length accorder, class the average length accorder, class the average cond-order, class the average conders accuracy for the second accuracy for the second accuracy for the second accuracy for the second accuracy Refers to the accuracy Refers to the accuracy Refers to the accuracy condens to the second accuracy: Verage Control Point 1st Order, Class I	ontal and vert ass II horizon gth line of 12 ass II levelin of the distance mile (that i i) = 0.01 mete or horizontal or coordinates (1986), then Second, if the cence Network 0.1 meter. If eific dataset, of Spacing (ft) meters 0.000	curacy of to ical survey tal survey, 000 feet: g survey (te in kilomes to say, 1 rs geodetic co are consist the networe NAD 83 co (HARN) adjuster val then those feet	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	and convert co say, 1:20, 1/20,000 = 0. say, 8 milling an average cers): ats can be est the original thas been deferming then the netwo cen determing and the determing and the determing and the determing are the result are	one Distance	in two way adjustment to seldom statewide acy has be etwork acc e of these (ft) mete	Propagated Error1 Error2 P.Error s. or regional en determination de	ole, ned to the area
apples for horizon accord-order, class I at Order, Class II	ontal and vert ass II horizon ith line of 12 ass II leveline of the distance in mile (that i i) = 0.01 meter is (1986), then Second, if the second, if the second if the s	curacy of to ical survey tal survey, 000 feet: g survey (te in kilomes to say, 1 rs geodetic contains the network NAD 83 con (HARN) adjuster value then those feet 0.000 0.000	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	and convert so say, 1:20, 1/20,000 = 0. say, 8 milling an average the original whas been deserved the network seen the network Horizontal A Average Lir 1st Order 2nd Order	one Distance	in two way adjustment to seldom statewide acy has be etwork acc e of these (ft) mete 0.000	Propagated Error1 Error2 P.Error s. for example or regional en determinacy for the general value of the gener	ole, ned to the area
mples for horizone cond-order, class I and Order, C	contal and vert ass II horizon it line of 12 is II leveline of the distance mile (that i. if a coordinates it (1986), then second, if the cence Network it Spacing (ft) meters 0.000 0.000	curacy of tical survey tal survey, 000 feet: g survey (te in kilomes to say, 1 rs geodetic co are consist the networe NAD 83 co (HARN) adjuster val then those feet 0.000 0.000	che points, ys are: (that is to 12,000 x 1 that is to eters) with 1.6 kilomet ontrol point stent with ck accuracy ordinates astment, th ues have b	and convert co say, 1:20, 1/20,000 = 0. say, 8 milling an average the original of the network	one Distance or, Class I	in two way adjustment to seldom statewide acy has be etwork acc e of these (ft) mete 0.000 0.000	Propagated Error1 Error2 P.Error S. or regional en determinaracy for trace general value of the control of the	ole, ned to che area

USACE Survey Marker Archiv	ve & Retrieval T	ool Datash	eet Type: Ne	w
Designation: BM/HS-AME-204-CHI Project: 213002 NRT CHICAGO RIVER Stamping: BM/HS-AME-204-CHI CDO 1985 PID NGS: NA COE: State: Illinois County: COOK District: Chicago Nearest Town: CHICAGO USGS Quad: LOOP T.R.S.: T39N R14E S4 Nearest Hwy/Mi: I-90/I-94, 1 MILE				DISK
Date Recovered: 01/30/2013	- Horizoi	ntal -	- 3 -	Vertical -
By: AMERICAN SURVEYING & ENGINEER !!	Datum: NAD83	(2011)	Datum: NAVD88	()
Condition/Stability: Good B	Lat: 41°53'59.7825"	N	Elevation Ht: 590.8	Ft Ft
Setting/Monument Type: BRASS DISK	Lon: -087°38'46.8867"	W	Ellip Ht:	11
Owner: ACOE	Local Accuracy: 2-cr	n	Local Accuracy:	2-cm
GPS Suitable: Yes No	NSRS Accuracy: 2-cr	n	NSRS Accuracy:	2-cm
Obstructions: N E S W	Survey/Computation RTK	Method:	Survey/Comp Geodetic Levels	utation Method:
Magnetic: Yes No	Date Observed: 01/30	/2013	Date Observed: 01	/30/2013 Geoid09
Access:	T	idal/Hydraulic	Gage Relationshi	nc -
Description/Comments: FOUND 3" BRASS DI CHICAGO RIVER. TO REACH MONUMENT FROM 0.25 MILES TO THE NORTHERLY ENTRANCE INTO		LK ALONG SEA WA	ALL ON THE SOUTH- DIVISION ST HEAD SO	OUTH ALONG HALSTED
THE NORTH LINE OF THE PROPERTY UNTIL YOU WEST OF THE SEA WALL AND +- 2.5' SOUTH OF T	REACH THE CHICAGO RI HE NORTHERLY END OF T	VER. MONUMENT HE WALK.	S IS SET ON THE CON	CRETE WALK +- 2.0 FEET
Zone 1: TL EAST Northing 1: 1906876.68	JSFT Easting 1: 117177	1.55 USFT Conv	rergence 1:	CSF 1:
	JSFT Easting 2:	USFT Conv		CSF 2:
- Horizon/Setup View -	60000		- Close-Up Vie	2W-
G SE	IMBER! GOISTANCE	CORPO	YEAR LO	AS CONTRACTOR OF THE PARTY OF T
Required Fields In Red	100000	Secretary and American	System Fields in G	reen II-SMART ver 5

Submit

System Fields in Green

U-SMART ver 5.0 23 AUG 2012

	7		
			, and .

with average length line of 12,000 feet: $12,000 \times 1/20,000 = 0.600$ feet · Second-order, class II leveling survey (that is to say, 8 millimeters per square-root of the distance in kilometers) with an average bench mark spacing of 1 mile (that is to say, 1.6 kilometers): $0.008 \times SQRT [1.6] = 0.01 meters$

the state of the s
ted Error Comp

Network accuracy for horizontal geodetic control points can be estimated in two ways. First, if the NAD 83 coordinates are consistent with the original NAD 83 adjustment, for example, the original NAD 83 (1986), then the network accuracy has been determined to seldom exceed 1.0 meters. Second, if the NAD 83 coordinates are the result of a statewide or regional High Accuracy Reference Network (HARN) adjustment, then the network accuracy has been determined to seldom exceed 0.05-0.1 meter. If better values have been determined for network accuracy for the area covered by the specific dataset, then those values should be used in place of these general values.

Vertical Accuracy:			
Average Control Point S	Spacing (ft)		
	meters	feet	
1st Order, Class I	0.000	0.000	
1st Order, Class II	0.000	0.000	
2nd Order, Class I	0.000	0.000	
2nd Order, Class II	0.000	0.000	
3rd Order	0.000	0.000	

Horizontal Accuracy:		
Average Line Distance	(ft)	
	meters	feet
1st Order	0.000	0.000
2nd Order, Class I	0.000	0.000
2nd Order, Class II	0.000	0.000
3rd Order, Class I	0.000	0.000
3rd Order, Class II	0.000	0.000
